

Forklift Attachment

Forklift Attachments Maine - Forklift attachments make a variety of jobs possible. There are numerous forklift attachments that make jobs faster and safer to complete. Besides regular forklift training, operators also need to undergo proper training for every attachment they will be using. Many hydraulic and non-hydraulic forklift attachments are available. They offer numerous benefits by decreasing man-power, employee accidents, fuel consumption, damage to stock and time. Equipment Considerations Forklift attachments can replace existing attachments or may be added to a machine that doesn't already have one. Several equipment-related factors must be considered before any forklift attachment is replaced or added. These considerations include: 1. The forklift type; 2. The forklift's capacity; 3. The carriage type; and 4. The number of hydraulic functions. Failure to properly consider these factors will increase the safety risk associated with operation of a forklift and its attachments and increase the risk for damage to the forklift, the attachment and surrounding area, including stock. There are further safety issues to take into consideration which can be discussed in more detail below. Forklift Rating and Re-Rating These machines are provided with lift capacity ratings from the manufacturer that need adjusting when changing or adding any forklift attachments. There are calculators available online from forklift attachment manufacturers to estimate each attachments particular lifting capacity. However, only the forklift manufacturer can provide accurate lifting capacities. The first step before installing any attachment is to get in touch with the authorized local forklift dealer to request that that forklift brand is re-rated accordingly with the attachment. After the manufacturer of the forklift has re-rated the forklift, it should have a new factory authorized specification plate. The upgraded specification plate replaces the original plate and needs to be installed with the new forklift rating showing. Equipment Upgrades When dealing with forklift attachments it is important to note that a forklift's hydraulic function is made up of a valve on the forklift with a lever located close to the operator which provides two passages of pressurized hydraulic oil to power the attachment features. Hydraulic forklift attachments typically offer numerous features compared to the number of valves on the forklift. Not every forklift attachment is hydraulic. When this happens, the forklift needs to have one or more valves added. There are numerous ways a valve can be added. Forklift manufacturers make accessories for valve and hose routing. There are plenty of labor and parts involved which can be costly enough to make this an impractical solution. Alternative methods include adding a solenoid valve in conjunction with a hose or cable reel that diverts oil flow from an existing function. Unfortunately, hose and cable reels can sometimes block the operator's view and can be easily damaged. Special hoses and a solenoid valve kit can be used to create an electrical conduit out of the reinforced braid. Since these hoses replace existing forklift hoses, they remain safe from external damage while maintaining clear vision for the operator. Safety Considerations Before using any type of forklift attachment, adequate training must be fulfilled. The operator needs to be able to remove, fit and operate the attachment. Two important safety factors must be considered before the use of any forklift attachment. First, any attachment on a forklift will reduce its nominal load rating, as mentioned above. The nominal load rating is computed with a stock fork carriage and forks. However, the actual load rating may be substantially lower. Secondly, the forklift's center of gravity will be affected when any forklift attachment is added. This will reduce the forklift's stability. Since the attachment's weight is prominent in front of the fulcrum point on the forklift, the operator needs to drive the machine as though it is partially loaded even before it is carrying a load. It is essential that operators travel slowly and make gentle turns when using any kind of forklift attachment. Check the forklift's capacity to ensure that every attachment is listed on the data plate. Specific safety checks must be made prior to using each forklift attachment. The attachment must be: 1. Appropriate for the specific forklift being used; 2. Appropriate for the specific load; 3. Attached correctly; 4. Properly locked; and 5. Permitted on the forklift's data plate. List of Common Forklift Attachments A list of the most common attachments and their general uses are set out below. There are numerous forklift

attachments and this list will cover the most popular. The variety of attachments can drastically increase efficiency for many jobs. **SIDESHIFTER:** The operator can manipulate the forks laterally with a sideshifter. This allows for easier load placement without having to move the entire forklift. **FORK POSITIONERS:** Moves the forks together or apart in relation to one another to adjust for various load types. **DIMENSIONING DEVICES:** Provide dimensions for the cargo allowing for more efficient use of warehouse and truck trailer space and often used in conjunction with billing systems based on volume. **ROTATOR:** Assists in righting skids that have tilted, handling custom load requirements and quick unloading. Many attachments include a rotator feature. **ROLL AND BARREL CLAMP:** The roll and barrel clamp allows the forklift to grasp rounded loads including barrels. It is outfitted with different pressure settings to facilitate fragile options and often has a rotate function to simplify horizontal and vertical positioning. **CARTON AND MULTIPURPOSE CLAMP:** Allows for grasping a load with a more squared shape, often with pressure settings. Products like cartons, boxes and bales can be moved with this type of attachment. **POLE ATTACHMENTS:** Long, metal pole used in place of forks to lift rolled items such as carpet or linoleum. **SLIP SHEETER OR PUSH-PULL:** Allows operator to transport slip sheets by clamping onto slip sheets, as opposed to pallets, and either pulling the slip sheet onto wide and thin metal forks for loading or pushing the slip sheet to unload. Some variations of the attachment are Save, where the slip sheet is removed for reuse, or Standard. **DRUM HANDLER:** Allows for grasping drums, either with a spring-loaded jaw to grip the top lip of a drum, or with arms that encircle the drum, for transport. **DRUM AND STORAGE BIN TIPPER:** Allows for quick transfer of loose or liquid contents in large containers. **MAN BASKET:** The lift platform known as a man basket is designed to transport workers vertically. It is outfitted with brackets and railings to anchor safety harnesses. **TELESCOPIC FORKS:** The telescopic forks are used in locations with a two pallet stacking design where one shelf is placed right behind another with no aisle between them. **SCALES:** Enables operators to simultaneously weigh and transport pallets, eliminating the need to interrupt transport to travel to scales, and can be obtained in legal-for-trade weights for operations that bill by weight. **SINGLE-DOUBLE FORKS:** Single-double forks facilitate movement of a single platform or pallet or two side-by-side pallets. This is useful for transporting specialty items with the right attachments employed. It can be used with normal lifting tasks and stops the need for owning two separate machines. This greatly reduces the cost of maintenance and operation that is used with multiple forklifts. **SNOW PLOW:** Originally designed for snow removal, snow plow attachments can be used to move other loose items. **SKIPS:** Skips facilitate fast and safe removal of waste to the proper waste or skip compactor. Skips are either a bottom-emptying model or a roll-forward type. **BOOMS AND JIBS:** Booms and jibs allow forklifts extended reach. They are available to transport deep or highly stacked loads, suspended loads and more. These attachments can be low profile, precision lifting or reach over models to facilitate extended lengths.